

# SAFETY DATA SHEET

## 1. Identification

**Product identifier** American Safety Tech. AS-250 Gray - Part A

**Other means of identification**

**SKU#** AS207R

**Recommended use** Not available.

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** ITW Engineered Polymers

**Address**  
130 Commerce Drive  
Montgomeryville, PA 18936  
United States

**Telephone** Customer Service 215-855-8450

**Website** www.itwengineeredpolymers.com

**E-mail** orders.na@itwep.com

**Contact person** EHS Department

**Emergency phone number** CHEMTREC 800-424-9300  
International 703-527-3887

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 3

**Health hazards** Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2

Sensitization, skin Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Warning

**Hazard statement** Flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.

**Storage** Store in a well-ventilated place. Keep cool.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information**

86.47% of the mixture consists of component(s) of unknown acute oral toxicity. 86.47% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 91.27% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 81.74% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**3. Composition/information on ingredients****Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Aluminium Oxide		1344-28-1	10 - 30
Crystalline SiO <sub>2</sub> (Quartz)		14808-60-7	10 - 30
Nepheline Syenite		37244-96-5	10 - 30
Epoxy Resin:--reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	5 - 10
1-methoxy-2-propanol		107-98-2	1 - 5
Methyl Amyl Ketone (MAK)		110-43-0	1 - 5
1,2,4-trimethylbenzene		95-63-6	1 - < 3
Aromatic Hydrocarbon Solvents		64742-95-6	1 - < 3
Xylene		1330-20-7	1 - < 3
Carbon Black		1333-86-4	0.1 - 1
Ethyl Benzene		100-41-4	0.1 - 1
Titanium Dioxide		13463-67-7	0.1 - 1
Other components below reportable levels			7 - 13

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**4. First-aid measures****Inhalation**

Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

**Eye contact**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion**

Rinse mouth. Get medical attention if symptoms occur.

**Most important symptoms/effects, acute and delayed**

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

**Indication of immediate medical attention and special treatment needed**

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

**General information**

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

**5. Fire-fighting measures****Suitable extinguishing media**

Water fog. Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

**Unsuitable extinguishing media**

Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical**

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Flammable liquid and vapor.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up** Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

**Precautions for safe handling** Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

**Conditions for safe storage, including any incompatibilities** Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Aluminium Oxide (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Aromatic Hydrocarbon Solvents (CAS 64742-95-6)	PEL	400 mg/m3	
		100 ppm	
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	PEL	0.05 mg/m3	
Ethyl Benzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Methyl Amyl Ketone (MAK) (CAS 110-43-0)	PEL	465 mg/m3	
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Aluminium Oxide (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
1-methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
Aluminium Oxide (CAS 1344-28-1)	TWA	50 ppm	
	TWA	1 mg/m3	Respirable fraction.
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm	
Methyl Amyl Ketone (MAK) (CAS 110-43-0)	TWA	50 ppm	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	

## US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1-methoxy-2-propanol (CAS 107-98-2)	STEL	25 ppm 540 mg/m3	
	TWA	150 ppm 360 mg/m3	
Aromatic Hydrocarbon Solvents (CAS 64742-95-6)	TWA	100 ppm 400 mg/m3	
	TWA	100 ppm 0.1 mg/m3	
Carbon Black (CAS 1333-86-4)	TWA	0.05 mg/m3	Respirable dust.
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	STEL	545 mg/m3	
Ethyl Benzene (CAS 100-41-4)	TWA	125 ppm 435 mg/m3	
	TWA	100 ppm 465 mg/m3	
Methyl Amyl Ketone (MAK) (CAS 110-43-0)	TWA	100 ppm	

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethyl Benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

### Exposure guidelines

#### US - California OELs: Skin designation

1-methoxy-2-propanol (CAS 107-98-2) Can be absorbed through the skin.

#### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Face shield is recommended. Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

#### Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** Liquid.

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Gray, Haze Gray, Black, Tile Red and Safety Yellow
<b>Odor</b>	Slight.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	> 240 °F (> 115.56 °C)
<b>Flash point</b>	> 81.0 °F (> 27.2 °C)
<b>Evaporation rate</b>	< 1 BuAc
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	8 mm Hg
<b>Vapor density</b>	> 1
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	748.4 °F (398 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	15.77 lb/gal
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IC estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Specific gravity</b>	1.89
<b>VOC</b>	2.07 lb/gal

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Halogens.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

## Information on toxicological effects

**Acute toxicity** Not known.

Components	Species	Test Results
1,2,4-trimethylbenzene (CAS 95-63-6)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 3160 mg/kg
Ethyl Benzene (CAS 100-41-4)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	3500 mg/kg
Methyl Amyl Ketone (MAK) (CAS 110-43-0)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	1.67 g/kg
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<b>Oral</b>		
LD50	Rat	3523 - 8600 mg/kg

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Risk of cancer cannot be excluded with prolonged exposure.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Crystalline SiO <sub>2</sub> (Quartz) (CAS 14808-60-7)	1 Carcinogenic to humans.
Ethyl Benzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

### US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

**Persistence and degradability**

**Bioaccumulative potential**

<b>Partition coefficient n-octanol / water (log Kow)</b>	
Ethyl Benzene	3.15
Methyl Amyl Ketone (MAK)	1.98
Xylene	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

#### DOT

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	III
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	B1, B52, IB3, T4, TP1, TP29
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242

#### IATA

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.

#### IMDG

<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	III
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	Not available.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.



Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

DOT



IATA; IMDG



## 15. Regulatory information

### US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

1-methoxy-2-propanol (CAS 107-98-2)	Listed.
Ethyl Benzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

1,2,4-trimethylbenzene (CAS 95-63-6)	% 1.0
Aluminium Oxide (CAS 1344-28-1)	% 1.0
Ethyl Benzene (CAS 100-41-4)	% 0.1
Xylene (CAS 1330-20-7)	% 1.0

#### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-trimethylbenzene (CAS 95-63-6)	Listed.
Aluminium Oxide (CAS 1344-28-1)	Listed.
Ethyl Benzene (CAS 100-41-4)	Listed.
Xylene (CAS 1330-20-7)	Listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
1,2,4-trimethylbenzene	95-63-6	1 - < 3
Aluminium Oxide	1344-28-1	10 - 30
Ethyl Benzene	100-41-4	0.1 - 1
Xylene	1330-20-7	1 - < 3

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethyl Benzene (CAS 100-41-4)  
Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Methyl Amyl Ketone (MAK) (CAS 110-43-0) Other Flavoring Substances with OSHA PEL's

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003  
Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7) Listed: October 1, 1988  
Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004  
Poly(p-phenylenediamine-co-terephthalolyl Chloride) (CAS 26125-61-1) Listed: July 1, 1990  
Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

Toluene (CAS 108-88-3) Listed: January 1, 1991

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

1,2,4-trimethylbenzene (CAS 95-63-6)  
1-methoxy-2-propanol (CAS 107-98-2)  
Aromatic Hydrocarbon Solvents (CAS 64742-95-6)  
Carbon Black (CAS 1333-86-4)  
Crystalline SiO<sub>2</sub> (Quartz) (CAS 14808-60-7)  
Ethyl Benzene (CAS 100-41-4)  
Titanium Dioxide (CAS 13463-67-7)  
Xylene (CAS 1330-20-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 03-31-2017

<b>Version #</b>	01
<b>HMIS® ratings</b>	Health: 2 Flammability: 3 Physical hazard: 0
<b>NFPA ratings</b>	Health: 2 Flammability: 3 Instability: 0
<b>Disclaimer</b>	ITW Engineered Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.
<b>Revision information</b>	This document has undergone significant changes and should be reviewed in its entirety.