



TECHNICAL DATA SHEET – TRAX COAT

Revised:4/2018

PRODUCT SPECIFICATION

Low Solar Absorbing LSA Acrylic copolymer one component anti-slip coating enhancer designed for application over non-skid deck coatings. Prevents loss of Coefficient of friction when coating over non-skids

Trax-Coat can be used for use on flight decks for VLA, safety markings, center lines and aesthetic enhancement. The product has a non-reflective matte appearance and provides maximum adhesion, toughness, wears resistance and excels in exterior weatherability. The pigments contain special colors which minimize Intra-red absorption and minimize deck temperatures.

SURFACE PREPARATION

Trax-Coat can be applied to any clean, dry surface, free of loose materials. Remove oil, grease, dirt and other foreign matter by cleaning with a water-based cleaner/ degreaser or approved cleaning solvent, then thoroughly flush with water and allow to dry.

MIXING AND APPLICATION

The container should be mixed thoroughly with an electric drill and a Jiffy® mixing blade for 3-5 minutes so that all material is uniform. The preferred method of application over non-skid is by a nap roller, but Trax-Coat can also be readily applied by brush or spray. For application of darker colors, one coat is sufficient. Where lighter colors are to be applied over a dark back ground, two coats are recommended with a second coat following first coat by about 24 hours.

SURFACE MAINTENANCE

To maintain a clean surface we recommend periodic cleaning with an approved all purpose, biodegradable cleaner/ degreaser. Scrub surface with a long-handled, fiber bristled brush or floor machine, rinse with water and allow drying.

TRAX COAT

LOW ABSORBING WATER BASED
ACRYLIC ANTI-SLIP ENHANCER

PRODUCT SPECIFICATIONS

GENERIC DESCRIPTION	LSA Water Based Acrylic Anti-Slip Enhancer
V.O.C	1.7 lbs per gallon (211 grams/ liter)
SOLIDS BY WEIGHT	39.5%
WEIGHT PER GALLON	9.6 lbs per gallon
ESTIMATE COVERAGE	320 sq. ft./ gal@ 5 mils WFT
STANDARD COLOR	Dark Gray (36076)
SHELF LIFE	1 Year
FLASH POINT	None (Water Based)
PACKAGING	5 Gallon Kit

Further product specifications adhere to manufactures ASTM F718.

The responsibility for surface preparation and product application rests with the customer. ITW Polymers Sealants North America, Inc. will assume no liability or imply any warranty as to the serviceability of the products or application due to the fact we have no control over surface preparation, environmental conditions or application procedures. ITW Polymers Sealants North America, Inc. technical assistance is advisory only unless otherwise specified.

CAUTION: Read Safety Data Sheet before using this material. Use only with adequate cross ventilation. Keep away from extreme heat, sparks and open flame. Keep from freezing. Avoid prolonged breathing of vapors. For dizziness, seek fresh air. Avoid contact with skin. Use gloves, goggles and coveralls. In case of spillage on clothing, change clothing to prevent prolonged contact with skin. Wash contaminated clothing before reuse. In case of accidental contact with skin, wash immediately with soap and water. In case of eye contact, flush thoroughly with plenty of water and call physician. If swallowed accidentally, do not induce vomiting. Seek medical attention immediately. The user of this product is responsible for making its own evaluation and tests regarding the capabilities, safety, utility, suitability and application of the product, and assumes all risks and liabilities resulting from the use or application of the product, whether used alone or with other products. ITW Polymers Sealants North America, Inc. (herein referenced to as the COMPANY) warrants only that the product conforms to the specifications contained in product Technical Data Sheets published By the COMPANY, a copy of which is available to the user. If the product fails to conform to this warranty, the user shall return the product within 10 days of the purchase date with a note specifying the defect and the COMPANY will either replace the product or at its option, return the purchase price. EXCEPT AS EXPRESSLY PROVIDED IN THIS PARAGRAPH, THE COMPANY MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND, NATURE OR DESCRIPTION, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE, AND HEREBY DISCLAIMS THE SAME. In no event shall the COMPANY be liable to the user of this product, whether in contract or in tort or any other legal theory (including, without limitation, negligence),for damages which exceed the purchase price of the product, or for any indirect, incidental, consequential or similar damages, arising out of sale, use or application of the product, or for any claim made against the user by any other party, even if ITW Polymers Sealants North America, Inc. has been advised of the possibility of such claim.