

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : SC-100 Part B

#### 1.2. Recommended use and restrictions on use

No additional information available

#### 1.3. Supplier

ITW Polymers and Sealants NA  
12055 Cutten Road  
Houston, TX 77066  
T 281-397-0033

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC (US Transportation): (800) 424-9300 International: +1 (703) 527-3887

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Acute Toxicity, Category 4 (Oral)	H302
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/irritation, Category 1	H318
Skin Sensitization, Category 1	H317
Reproductive Toxicity, Category 2	H361
Hazardous to the aquatic environment - Acute Hazard, Category 1	H400
Hazardous to the aquatic environment - Chronic Hazard, Category 1	H410

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H361 - Suspected of damaging fertility or the unborn child  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P260 - Do not breathe mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, eye protection, face protection, protective clothing.  
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%
Isophorone diamine	(CAS-No.) 2855-13-2	10 – 30
Benzyl alcohol	(CAS-No.) 100-51-6	10 – 30
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS-No.) 9046-10-0	10 – 30
phenol, 4-nonyl-, branched	(CAS-No.) 84852-15-3	10 – 30
1-(2-Aminoethyl) piperazine	(CAS-No.) 140-31-8	1 – 5

\*In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Causes severe skin burns and eye damage. Suspected of damaging fertility. Suspected of damaging the unborn child. Harmful if swallowed. May cause an allergic skin reaction.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : May cause an allergic skin reaction. Causes severe skin burns.
- Symptoms/effects after eye contact : Causes serious eye damage.
- Symptoms/effects after ingestion : Harmful if swallowed.
- Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Carbon dioxide. Foam. Dry powder. Sand.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Specific hazards arising from the chemical

- Fire hazard : No data available.
- Explosion hazard : No data available.
- Reactivity : No dangerous reactions known under normal conditions of use.

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use cold water spray to cool fire-exposed containers to minimize risk of rupture. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment/cleaning up : SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 6.4. Reference to other sections

See Sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : For professional or industrial use only. Follow label instructions. Keep out of reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a dry, cool and well-ventilated place. Keep container tightly closed.
- Special rules on packaging : Keep only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Isophorone diamine (2855-13-2)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
<b>Benzyl alcohol (100-51-6)</b>		
OSHA	Remark (OSHA)	OELs not established
AIHA	WEEL TWA [ppm]	10 ppm
<b>1-(2-Aminoethyl) piperazine (140-31-8)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
<b>phenol, 4-nonyl-, branched (84852-15-3)</b>		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ensure adequate ventilation, especially in confined areas.

### 8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing. In case of inadequate ventilation wear respiratory protection.

#### Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

#### Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to airborne particles.

#### Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

#### Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment. An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Viscous liquid.  
Color : Clear  
Odor : Amine

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 93.3 °C (200 °F)
Relative evaporation rate (n-butyl acetate =1)	: < 1
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Density	: 8.2 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Isophorone diamine (2855-13-2)

LD50 oral rat	1030 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	1.07 – 5.01 mg/l/4h

#### Benzyl alcohol (100-51-6)

LD50 oral rat	1230 mg/kg
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 Inhalation - Rat	> 4178 mg/m <sup>3</sup> (Exposure time: 4 h)

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>1-(2-Aminoethyl) piperazine (140-31-8)</b>	
LD50 oral rat	2140 mg/kg
LD50 dermal rabbit	880 µl/kg
<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>	
LD50 oral rat	242 mg/kg
LD50 dermal rabbit	2980 mg/kg
LC50 Inhalation - Rat	> 0.74 mg/l (Exposure time: 8 h)
<b>phenol, 4-nonyl-, branched (84852-15-3)</b>	
LD50 oral rat	1300 mg/kg
LD50 dermal rabbit	2031 mg/kg

Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: Causes severe skin burns and eye damage. Suspected of damaging fertility. Suspected of damaging the unborn child. Harmful if swallowed. May cause an allergic skin reaction.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Causes severe skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: No data available.
Hazardous to the aquatic environment, short-term (acute)	: Toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

No additional information available

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods	: Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Transport document description (DOT) : UN3066 Paint related material (Contains: phenol, 4-nonyl-, branched), 8, III  
UN-No.(DOT) : UN3066  
Proper Shipping Name (DOT) : Paint related material  
phenol, 4-nonyl-, branched  
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136  
Packing group (DOT) : III - Minor Danger  
Hazard labels (DOT) : 8 - Corrosive



Dangerous for the environment : Yes  
Marine pollutant : Yes

DOT Quantity Limitations Passenger aircraft/rail : 5 L  
(49 CFR 173.27)  
DOT Quantity Limitations Cargo aircraft only (49 : 60 L  
CFR 175.75)  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a  
passenger vessel.  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"  
Emergency Response Guide (ERG) Number : 153  
Other information : No supplementary information available.

#### Transport by sea (IMDG)

Transport document description (IMDG) : UN 3066 PAINT (Contains: phenol, 4-nonyl-, branched), 8, III  
UN-No. (IMDG) : 3066  
Proper Shipping Name (IMDG) : PAINT  
Class (IMDG) : 8 - Corrosive substances  
Packing group (IMDG) : III - substances presenting low danger  
Limited quantities (IMDG) : 5 L  
Marine pollutant : Yes

#### Air transport (IATA)

Transport document description (IATA) : UN 3066 Paint related material (Contains: phenol, 4-nonyl-, branched), 8, III  
UN-No. (IATA) : 3066  
Proper Shipping Name (IATA) : Paint related material  
Class (IATA) : 8 - Corrosives  
Packing group (IATA) : III - Minor Danger

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

# SC-100 Part B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SC-100 Part B	
All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA.	
SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Acute toxicity (any route of exposure) Health hazard - Reproductive toxicity

### 15.2. International regulations

No additional information available


### 15.3. US State regulations

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Component	State or local regulations
Isophorone diamine(2855-13-2)	U.S. - New Jersey - Right to Know Hazardous Substance List
Benzyl alcohol(100-51-6)	U.S. - Pennsylvania - RTK (Right to Know) List
1-(2-Aminoethyl) piperazine(140-31-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

### SECTION 16: Other information

Other information	: Author: JAD.
NFPA health hazard	: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Material that in themselves are normally stable, even under fire conditions.
HMIS Hazard Rating	
Health	: 3*
	* - Chronic (long-term) health effects may result from repeated overexposure
Flammability	: 1
Physical	: 0



*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*