

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : MS-8CZ Part B

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

ITW Polymers and Sealants NA
12055 Cutten Road
Houston, TX 77066
T 281-397-0033

1.4. Emergency telephone number

Emergency number : CHEMTREC (US Transportation): (800) 424-9300 International: +1 (703) 527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids, Category 3	H226
Acute toxicity (oral), Category 4	H302
Skin corrosion/irritation, Category 1B	H314
Serious eye damage/irritation, Category 1	H318
Skin sensitization, Category 1	H317
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment - Acute Hazard, Category 1	H400
Hazardous to the aquatic environment - Chronic Hazard, Category 2	H411

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H226 - Flammable liquid and vapor.
H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H361 - Suspected of damaging fertility or the unborn child.
H400 - Very toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, eye protection, face protection, protective clothing.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of soap and water.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P310 - Immediately call poison center/doctor/...
P330 - Rinse mouth.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Tall oil fatty acids, reaction product with Tetraethylene pentamine	(CAS-No.) 68953-36-6	15 – 40
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine	(CAS-No.) 68082-29-1	10 – 30
1,3-Benzenedimethanamine	(CAS-No.) 1477-55-0	10 – 30
N-(3-Aminopropyl)morpholine	(CAS-No.) 123-00-2	10 – 30
Cashew, nutshell liquid	(CAS-No.) 8007-24-7	7 – 13
Benzyl alcohol	(CAS-No.) 100-51-6	5 – 10
4-tert-Butylphenol	(CAS-No.) 98-54-4	5 – 10
Tetraethylenepentamine	(CAS-No.) 112-57-2	3 – 7
Trimethylhexamethylenediamine	(CAS-No.) 25620-58-0	1 – 5
Benzene, 1,2,4-trimethyl-	(CAS-No.) 95-63-6	1 – 5

* In accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200), the specific chemical identity or exact weight % has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects : Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child.
- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Causes severe skin burns. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Causes serious eye damage.

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion : Harmful if swallowed.
Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Carbon dioxide. Foam. Dry powder. Sand.
Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard : Flammable liquid and vapor.
Explosion hazard : No data available.
Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use cold water spray to cool fire-exposed containers to minimize risk of rupture. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained cleaning personnel properly equipped with respiratory and eye protection.

6.1.1. For non-emergency personnel

Protective equipment : Wear Protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing, gloves and eye or face protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment/cleaning up : SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

6.4. Reference to other sections

See Sections 8 and 13.

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : For professional or industrial use only. Follow label instructions. Keep out of reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Store in original container. Keep container closed when not in use. Containers which are opened should be properly resealed and kept upright to prevent leakage.

Heat and ignition sources : Avoid ignition sources.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Cashew, nutshell liquid (8007-24-7)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Tetraethylenepentamine (112-57-2)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
AIHA	WEEL TWA	5 mg/m ³
1,3-Benzenedimethanamine (1477-55-0)		
ACGIH	ACGIH OEL C	0.1 mg/m ³
ACGIH	ACGIH OEL C [ppm]	0.018 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye, skin, & GI irr. Notations: Skin
ACGIH	Regulatory reference	ACGIH 2022
OSHA	OSHA PEL C	0.1 mg/m ³ Vacated
NIOSH	NIOSH REL C	0.1 mg/m ³
NIOSH	US-NIOSH chemical category	Potential for dermal absorption
Benzyl alcohol (100-51-6)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
AIHA	WEEL TWA [ppm]	10 ppm
4-tert-Butylphenol (98-54-4)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Trimethylhexamethylenediamine (25620-58-0)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

N-(3-Aminopropyl)morpholine (123-00-2)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established
Benzene, 1,2,4-trimethyl- (95-63-6)		
ACGIH	ACGIH OEL TWA [ppm]	10 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: CNS impair; hematologic eff. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH	Regulatory reference	ACGIH 2022
OSHA	Remark (OSHA)	OELs not established
NIOSH	NIOSH REL TWA	125 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	25 ppm
Tall oil fatty acids, reaction product with Tetraethylene pentamine (68953-36-6)		
ACGIH	Remark (ACGIH)	OELs not established
OSHA	Remark (OSHA)	OELs not established

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment symbol(s):



Personal protective equipment:

Gloves. Protective goggles. Protective clothing. In case of inadequate ventilation wear respiratory protection.

Hand protection:

Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection:

Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to airborne particles.

Skin and body protection:

Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection:

Use NIOSH (or other equivalent national standard) -approved dust/particulate respirator. Where dust exceeds PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid
Color	: Amber
Odor	: Slight
Odor threshold	: No data available
pH	: No data available

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Melting point	: No data available
Freezing point	: No data available
Boiling point	: 176.67 °C (350.01 °F) estimated
Flash point	: > 40.6 °C (105 °F)
Relative evaporation rate (n-butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 1.18 hPa estimated
Relative vapor density at 20 °C	: No data available
Relative density	: 0.97
Density	: 8.07 lb/gal
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: 435 °C (815 °F)
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : 0.54 lb/gal mixed components

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid contact with incompatible materials. Ignition sources. Heat. Sparks. Open flame. Static electricity.

10.5. Incompatible materials

Alkali metals. Peroxides. Phenols.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Cashew, nutshell liquid (8007-24-7)

LD50 oral rat	> 1000 mg/kg
LD50 dermal rat	> 2000 mg/kg

Tetraethylenepentamine (112-57-2)

LD50 oral rat	2100 mg/kg
LD50 dermal rabbit	660 µl/kg

1,3-Benzenedimethanamine (1477-55-0)

LD50 oral rat	660 mg/kg
LD50 dermal rat	> 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LD50 dermal rabbit	2 g/kg
LC50 Inhalation - Rat	1.16 mg/l/4h

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1,3-Benzenedimethanamine (1477-55-0)	
LC50 Inhalation - Rat [ppm]	700 ppm/1h
Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rat	2000 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 Inhalation - Rat	> 4178 mg/m ³ (Exposure time: 4 h)
4-tert-Butylphenol (98-54-4)	
LD50 oral rat	2990 mg/kg
LD50 dermal rabbit	2318 mg/kg
Trimethylhexamethylenediamine (25620-58-0)	
LD50 oral rat	910 mg/kg
N-(3-Aminopropyl)morpholine (123-00-2)	
LD50 oral rat	1790 mg/kg
LD50 dermal rabbit	2219.7 – 2396.1 mg/kg
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 Inhalation - Rat	18 g/m ³ (Exposure time: 4 h)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects	: Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes severe skin burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

- Ecology - general : No information available.
- Hazardous to the aquatic environment, short-term (acute) : Very toxic to aquatic life.
- Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description (DOT) : UN3470 Paint, corrosive, flammable (contains Tall oil fatty acids, reaction product with Tetraethylene pentamine, N-(3-Aminopropyl)morpholine), 8 (3), II
- UN-No.(DOT) : UN3470
- Proper Shipping Name (DOT) : Paint, corrosive, flammable
(contains Tall oil fatty acids, reaction product with Tetraethylene pentamine, N-(3-Aminopropyl)morpholine)
- Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
- Packing group (DOT) : II - Medium Danger
- Subsidiary risk (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 8 - Corrosive
3 - Flammable liquid



- Dangerous for the environment : Yes
- Marine pollutant : Yes



- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
- DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
- Emergency Response Guide (ERG) Number : 132
- Other information : No supplementary information available.

Transport by sea (IMDG)

- Transport document description (IMDG) : UN 3470 PAINT, CORROSIVE, FLAMMABLE (contains Tall oil fatty acids, reaction product with Tetraethylene pentamine, N-(3-Aminopropyl)morpholine), 8 (3), II
- UN-No. (IMDG) : 3470
- Proper Shipping Name (IMDG) : PAINT, CORROSIVE, FLAMMABLE
- Class (IMDG) : 8 - Corrosive substances
- Packing group (IMDG) : II - substances presenting medium danger
- Subsidiary hazard (IMDG) : 3 - Flammable liquids

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Limited quantities (IMDG) : 1 L
Marine pollutant : Yes



Air transport (IATA)

Transport document description (IATA) : UN 3470 Paint, corrosive, flammable (contains Tall oil fatty acids, reaction product with Tetraethylene pentamine, N-(3-Aminopropyl)morpholine), 8 (3), II
UN-No. (IATA) : 3470
Proper Shipping Name (IATA) : Paint, corrosive, flammable
Class (IATA) : 8 - Corrosives
Packing group (IATA) : II - Medium Danger
Subsidiary hazards (IATA) : 3 - Flammable liquids

SECTION 15: Regulatory information

15.1. US Federal regulations

MS-8CZ Part B	
All chemical substances in this product are listed as "Active" in the EPA (Environmental Protection Agency) "TSCA Inventory Notification (Active-Inactive) Requirements Rule" ("the Final Rule") of Feb. 2019, as amended Feb. 2021, or are otherwise exempt or regulated by other agencies such as FDA or FIFRA.	
SARA Section 311/312 Hazard Classes	Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Reproductive toxicity

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Cumene (98-82-8)	X					

Component	State or local regulations
Tetraethylenepentamine (112-57-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
1,3-Benzenedimethanamine (1477-55-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List
Benzyl alcohol (100-51-6)	U.S. - Pennsylvania - RTK (Right to Know) List
Trimethylhexamethylenediamine (25620-58-0)	U.S. - New Jersey - Right to Know Hazardous Substance List
N-(3-Aminopropyl)morpholine (123-00-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Benzene, 1,2,4-trimethyl- (95-63-6)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

MS-8CZ Part B

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances
Xylene (1330-20-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Phenol (108-95-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List


SECTION 16: Other information

Other information : Author: EMA.

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMIS Hazard Rating

Health : 3*
* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 1

Physical : 0

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.